



AL-D19 WATER COOLER AL-SD19 WATER COOLER SERIES



- 3.3L Stainless Steel Cold Tank; up to 3.2L of Chilled Water Per Hour
- 1.8L Hot Tank; up to 2.55L of Hot Water Per Hour
- Stylish High-Gloss Black and Stainless Steel Look Cabinet
- Available in Hot/Cold or Cool/Cold
- Hygienic Push Taps
- Connects to Mains Water Supply
- Complete with the Aqua L'eau Dual Water Filtration System
- Access Plate on the Side of AL-SD19C
- 36-Month Comprehensive Warranty



www.aqualeau.com.au

@aqualeau_



AL-D19 AL-SD19 WATER COOLER

SERIES

GENERAL FEATURES

Featuring a high-gloss front, brushed steel sides and a stylish slim design, the AL-D19 Series Water Cooler is perfect for any home or office.

COLD TANK: 3.3-litre Type 304 stainless steel tank for superior chilling. The highly polished surface makes it easy to clean and maintain.

HOT TANK: 1.8-litre Type 304 stainless steel with 500-watt sheathed heater ensures precise temperature control. The on/off switch is easily accessible at the back of the unit.

CABINET: High-gloss black front with brushed silver steel sides. The top and front panels are moulded ABS plastic, the side panels are high polymer coated steel.

TAPS: NSF-approved, hygienic and durable polypropylene push taps with self-closing design and fast flow. Hot safety tap comes as standard on hot/cold model.

FLOAT ASSEMBLY: Dual float system maintains the water level and shuts off when full.

WATER FILTRATION: An external Aqua L'eau Dual Water Filtration System reduces sediment, chemicals, organic compounds and impurities, which can adversely affect the quality and taste of your drinking water.

OPTIONAL EXTRAS

AL-CD WHITE OR BLACK: Our cup dispensers come in black or white to match either colour unit. The Aqua L'eau paper and plastic cups are designed to fit our dispensers.

INSTALLATION

To be installed in accordance with local plumbing laws. Failure to install a certified Pressure Limiting Valve will void warranty.

SPECIFICATIONS

REFRIGERATION: Gas R134A. The refrigerant flow is controlled by a capillary tube which has no moving parts. The compressor is hermetically sealed with an automatic overload protector. Lubricant is not needed.

ELECTRICAL: Certificate number 160793. 220v 50hz single phase. A 1.5-metre power cord is supplied. Full load current is 1.2 amps.

CONDENSER: Quietly operating, air cooled with no moving parts.

PERFORMANCE

Tap 1	Approx. 4-10°C
Tap 2	Room Temperature
Hot tap	Approx. 84-89°C

ROOM TEMP °C	21	27	32
150ML CUPS/HR 10°C	22	17	13
LITRES/HR AT 10°C	3.2	2.6	2
HOT WATER DELIVERY: 15 x 170ml cups per hour			

**Intermittent use only, continuous use will result in reduced performance.*

SHIPPING WEIGHTS & DIMENSIONS

MODEL	WEIGHT	MODEL	WEIGHT	WIDTH	DEPTH	HEIGHT
AL-D19C	17kg	D19CH	19kg	29cm	34cm	100cm
AL-SD19C	16kg	SD19CH	18kg	29cm	51cm	53cm

WARRANTY

The Aqua L'eau AL-D19 Series is covered by our 36-month Comprehensive Warranty (copy available on request). The warranty provides comprehensive parts and labour coverage for the period of 36 months from the date of original sale.