



# AL-D19 WATER COOLER AL-SD19 WATER COOLER SERIES



- 3.3L Stainless Steel Cold Tank; up to 3.2L of Chilled Water Per Hour
- 1.8L Hot Tank; up to 2.55L of Hot Water Per Hour
- Stylish High-Gloss White and Stainless Steel Look Cabinet
- Available in Hot/Cold or Cool/Cold
- Hygienic Push Taps
- Connects to Mains Water Supply
- Complete with the Aqua L'eau Dual Water Filtration System
- Access Plate on the Side of AL-SD19C
- 36-Month Comprehensive Warranty



[www.aqualeau.com.au](http://www.aqualeau.com.au)

@aqualeau\_



# AL-D19 AL-SD19 WATER COOLER

## SERIES

### GENERAL FEATURES

Featuring a high-gloss front, brushed steel sides and a stylish slim design, the AL-D19 Series Water Cooler is perfect for any home or office.

**COLD TANK:** 3.3-litre Type 304 stainless steel tank for superior chilling. The highly polished surface makes it easy to clean and maintain.

**HOT TANK:** 1.8-litre Type 304 stainless steel with 500-watt sheathed heater ensures precise temperature control. The on/off switch is easily accessible at the back of the unit.

**CABINET:** High-gloss white front with brushed silver steel sides. The top and front panels are moulded ABS plastic, the side panels are high polymer coated steel.

**TAPS:** NSF-approved, hygienic and durable polypropylene push taps with self-closing design and fast flow. Hot safety tap comes as standard on hot/cold model.

**FLOAT ASSEMBLY:** Dual float system maintains the water level and shuts off when full.

**WATER FILTRATION:** An external Aqua L'eau Dual Water Filtration System reduces sediment, chemicals, organic compounds and impurities, which can adversely affect the quality and taste of your drinking water.

### OPTIONAL EXTRAS

**AL-CD WHITE OR BLACK:** Our cup dispensers come in black or white to match either colour unit. The Aqua L'eau paper and plastic cups are designed to fit our dispensers.

### INSTALLATION

To be installed in accordance with local plumbing laws. Failure to install a certified Pressure Limiting Valve will void warranty.

### SPECIFICATIONS

**REFRIGERATION:** Gas R134A. The refrigerant flow is controlled by a capillary tube which has no moving parts. The compressor is hermetically sealed with an automatic overload protector. Lubricant is not needed.

**ELECTRICAL:** Certificate number 160793. 220v 50hz single phase. A 1.5-metre power cord is supplied. Full load current is 1.2 amps.

**CONDENSER:** Quietly operating, air cooled with no moving parts.

### PERFORMANCE

Tap 1	Approx. 4-10°C
Tap 2	Room Temperature
Hot tap	Approx. 84-89°C

ROOM TEMP °C	21	27	32
150ML CUPS/HR 10°C	22	17	13
LITRES/HR AT 10°C	3.2	2.6	2
HOT WATER DELIVERY: 15 x 170ml cups per hour			

*\*Intermittent use only, continuous use will result in reduced performance.*

### SHIPPING WEIGHTS & DIMENSIONS

MODEL	WEIGHT	MODEL	WEIGHT	WIDTH	DEPTH	HEIGHT
AL-D19C	17kg	D19CH	19kg	29cm	34cm	100cm
AL-SD19C	16kg	SD19CH	18kg	29cm	51cm	53cm

### WARRANTY

The Aqua L'eau AL-D19 Series is covered by our 36-month Comprehensive Warranty (copy available on request). The warranty provides comprehensive parts and labour coverage for the period of 36 months from the date of original sale.