



AL-D25 WATER COOLER

SERIES



- Large 11L Cold Tank; up to 5.2L of Chilled Water Per Hour
- 1.6L Hot Tank; up to 2.55L of Hot Water Per Hour
- Available in Black or White with a Satin Finish
- Available in Hot/Cold or Cool/Cold
- Hygienic Push Taps
- Connects to Mains Water Supply
- Complete with the Aqua L'eau Dual Water Filtration System
- Easy to Clean and Sanitise
- 36-Month Comprehensive Warranty



WaterMark
ATSS200.105
WM-022458



www.aqualeau.com.au

@aqualeau_



AL-D25 WATER COOLER

SERIES

GENERAL FEATURES

The AL-D25 Series, featuring an elegant satin finish, is the latest addition to our range of POU water coolers and adds a touch of class to any home or office.

COLD TANK: Huge 11-litre, high density polypropylene tank designed to be tough, rustproof and is easy to clean with its large radius.

HOT TANK: 1.6-litre Type 304 stainless steel with 500-watt sheathed heater ensures precise temperature control. The on/off switch is easily accessible at the back of the unit.

CABINET: Available in satin black or white, with U.V. treated ABS top and front panels and zinc-coated steel side panels.

TAPS: NSF-approved, hygienic, durable polypropylene push taps with self-closing design and fast flow. Hot safety tap comes as standard on hot/cold model.

FLOAT ASSEMBLY: Dual float system maintains the water level and shuts water off when tank is full.

WATER FILTRATION: An external Aqua L'eau Dual Water Filtration System reduces sediment, chemicals, organic compounds and impurities, which can adversely affect the quality and taste of your drinking water.

OPTIONAL EXTRAS

AL-CD WHITE OR BLACK: Our cup dispensers come in black or white to match either colour unit. The Aqua L'eau paper and plastic cups are designed to fit our dispensers.

INSTALLATION

To be installed in accordance with local plumbing laws. Failure to install a certified Pressure Limiting Valve will void warranty.

SPECIFICATIONS

REFRIGERATION: Gas R134A. The refrigerant flow is controlled by a capillary tube which has no moving parts. The compressor is hermetically sealed with an automatic overload protector. Lubricant is not needed.

ELECTRICAL: Certificate number 160793. 220v 50hz single phase. A 1.5-metre power cord is supplied. Full load current is 1.2 amps.

CONDENSER: Quietly operating, air cooled with no moving parts.

PERFORMANCE

Tap 1	Approx. 4-10°C
Tap 2	Room Temperature
Hot tap	Approx. 84-89°C

ROOM TEMP °C	21	27	32
150ML CUPS/HR 10°C	35	28	16
LITRES/HR AT 10°C	5.2	4.2	2.4
HOT WATER DELIVERY: 15 x 170ml cups per hour			

**Intermittent use only, continuous use will result in reduced performance.*

SHIPPING WEIGHTS & DIMENSIONS

MODEL	WEIGHT	MODEL	WEIGHT	WIDTH	DEPTH	HEIGHT
AL-D25	21kg	D25CH	23kg	33cm	39cm	115cm

WARRANTY

The Aqua L'eau AL-D25 Series is covered by our 36-month Comprehensive Warranty (copy available on request). The warranty provides comprehensive parts and labour coverage for the period of 36 months from the date of original sale.