



AL-D5 WATER COOLER

SERIES



- 💧 The Most Reliable POU Cooler on the Market
- 💧 Huge 14.3L Cold Tank; up to 6.6L of Chilled Water Per Hour
- 💧 1.8L Hot Tank; up to 1.8L of Hot Water Per Hour
- 💧 Available in Bench Top or Floor Standing and Hot/Cold or Cool/Cold
- 💧 Hygienic Push Taps
- 💧 Connects to Mains Water Supply
- 💧 Complete with the Aqua L'eau Dual Water Filtration System
- 💧 Easy to Clean and Sanitise
- 💧 36-Month Comprehensive Warranty



WaterMark
ATSS200.105
WM-022458



www.aqualeau.com.au

@aqualeau_



AL-D5 WATER COOLER

SERIES

GENERAL FEATURES

The AL-D5 Series sets the standard for entry-level POU water coolers. While often copied, none have matched the quality or longevity of the AL-D5 Series.

COLD TANK: Huge 14.3-litre, high density polypropylene tank designed to be tough, rustproof and is easy to clean with its large radius.

HOT TANK: 1.8-litre Type 304 stainless steel with 500-watt sheathed heater ensures precise temperature control. The on/off switch is easily accessible at the back of the unit.

CABINET: Gloss Cloud White finish with U.V. treated ABS top and front panels. Side panels are zinc-coated steel, covered with a polymer polyester resin.

TAPS: NSF-approved, durable polypropylene lever-type taps with a self-closing design and fast flow. Hot safety tap comes as standard on hot/cold model. Optional push taps now available.

FLOAT ASSEMBLY: One stage polyethylene float system maintains the water level and shuts off when full.

WATER FILTRATION: An external Aqua L'eau Dual Water Filtration System reduces sediment, chemicals, organic compounds and impurities, which can adversely affect the quality and taste of your drinking water.

OPTIONAL EXTRAS

AL-CD2 – CUP DISPENSER: The AL-CD2 is perfectly colour matched to suit the Aqua L'eau Series Water Cooler Range. The Aqua L'eau paper and plastic cups are specifically made to fit the AL-CD2.

INSTALLATION

To be installed in accordance with local plumbing laws. Failure to install a certified Pressure Limiting Valve will void warranty.

SPECIFICATIONS

REFRIGERATION: Gas R134A. The refrigerant flow is controlled by a capillary tube which has no moving parts. The compressor is hermetically sealed with an automatic overload protector. Lubricant is not needed.

ELECTRICAL: Certificate number 160793. 220v 50hz single phase. A 1.5-metre power cord is supplied. Full load current is 1.2 amps.

CONDENSER: Quietly operating, air cooled with no moving parts.

PERFORMANCE

Tap 1	Approx. 4-10°C
Tap 2	Room Temperature
Hot tap	Approx. 84-89°C

CAPACITY

ROOM TEMP °C	150ML CUPS/HR 10°C	LITRES/HR AT 10°C
21°C	44	6.6
27°C	32	4.8
32°C	18	2.7

SHIPPING WEIGHTS & DIMENSIONS

MODEL	WEIGHT	MODEL	WEIGHT	WIDTH	DEPTH	HEIGHT
AL-D5C	19kg	D5CH	21kg	33cm	33cm	115cm
AL-SD5C	16kg	SD5CH	18kg	33cm	33cm	70cm

WARRANTY

The Aqua L'eau Series is covered by our 36-month Comprehensive Warranty (copy available on request). The warranty provides comprehensive parts and labour coverage for the period of 36 months from the date of original sale.