



AL-IC1000 WATER CHILLER

REMOTE COOLING & STORAGE SYSTEMS



- 60L Storage
- Stainless Steel Reservoir
- Cools 120L Per Hour
- Serves up to 6 Outlets
- Heavy-Duty Construction
- Designed and Built in Australia
- Superior Insulation and Energy Efficiency
- 12-Month Comprehensive Wholesale Warranty
- Ideal for Schools, Mines, Sports Facilities, Dining Halls and other High Demand Applications



WaterMark
WMTS-105:2016
WM-022633



www.aqualeau.com.au

@aqualeau_



AL-IC1000 WATER CHILLER

REMOTE COOLING & STORAGE SYSTEMS

GENERAL INFORMATION

The Aqua L'eau AL-IC1000 water cooling and storage system provides enough cold water to cope with the most extreme periods of high demand. The combination of extreme cooling performance and a significant volume of stored cold water make these coolers ideal for many applications such as public access areas, schools, mines, construction sites and sporting venues.

The AL-IC1000 is a remote cooling system that can be installed in-line prior to whichever tapware is most appropriate for the application. Whether that be a single faucet for high volume draw-off, or a trough with up to 6 bubbler faucets for schools or sporting clubs (see picture for example).

COOLING SYSTEM

The AL-IC1000's cooling system features industry-leading technology with a hermetically sealed dynamic condensing unit. Superior insulation prevents heat gain, enhancing energy efficiency. The sealed unit contains 330 grams of ozone-friendly R134a refrigerant.

INSTALLATION

The universal design of the AL-IC1000 allows for easy installation. Commonly installed in-line to supply cooled water to bubbler troughs (shown below), it can also support varied applications. The included 1.2-metre cord with 3-pin plug connects to any Australian Standard 240V, 50Hz single-phase power outlet. Plumbing connections (inlet and outlet) are 1/2" male BSP threaded.

To install the AL-IC1000, position it upright in a sheltered area away from the elements on a flat, stable surface. Ensure adequate ventilation space and easy access to the service panel for optimal operation.

WARRANTY

The AL-IC1000 is covered by the Aqua L'eau Warranty, (copy available on request). This provides 12 months of comprehensive coverage, inclusive of parts and labour.

CAPACITY

MODEL	AL-IC1000
DESCRIPTION	REMOTE CHILLER
RESERVOIR VOLUME	60 LITRES
LITRES / HOUR	120 LPH
OUTLETS	UP TO 6
PACKED WEIGHT	55kg
UNPACKED DIMENSIONS	530W X 870D X 640H
UNPACKED WEIGHT	50kg

Typical installation of Remote AL-IC1000 with bubbler trough, (not furnished with cooler).

