



AL-IC8 WATER CHILLER

REMOTE/UNDERSINK CHILLER



- 💧 Lead and Copper-Free Construction
- 💧 1.9L Stainless Steel Chilling Tank
- 💧 8L Per Hour Cooling Capacity
- 💧 Stainless Steel Internal Construction
- 💧 Powder-Coated Corrosion Resistant Cabinet
- 💧 8-Cup Initial Draw-off
- 💧 Dual, Fan Assisted Static Condensers
- 💧 3-Year Comprehensive Warranty
- 💧 Complete with the Aqua L'eau Dual Water Filtration System



WaterMark
ATSS200.105
WM-022458



www.aqualeau.com.au

@aqualeau_



AL-IC8 WATER CHILLER

REMOTE/UNDERSINK CHILLER

With its 8-litre per hour cooling capacity, the Aqua L'eau AL-IC8 is proof that good things come in small packages. Due to the compact design, energy efficiency and quiet operation the AL-IC8 Undersink chiller is the obvious choice for household applications and offices alike.

SPECIFICATIONS

CABINET: The cabinet is a corrosion resistant, high polymer polyester coated steel panel.

COLD WATER TANK: 1.7-litre fully insulated, 304 stainless steel tank. The drain plug and seal are removable for servicing.

REFRIGERATION SYSTEM: This fan assisted, static condenser system utilises R134a refrigerant which is non toxic, non-flammable and non ozone depleting. Refrigerant flow is controlled by capillary tube, which has no moving parts. The compressor is protected by an automatic overload, is lifetime lubricated and hermetically sealed.

WATER FILTRATION: An external Aqua L'eau Dual Water Filtration System reduces sediment, chemicals, organic compounds and impurities, which can adversely affect the quality and taste of your drinking water.

INSTALLATION

To be installed in accordance with local plumbing laws. Failure to install a certified Pressure Limiting Valve will void warranty.

GENERAL: The Aqua L'eau AL-IC8 can be installed in small spaces with adequate ventilation and can be used in conjunction with most inline filter systems. The AL-IC8 must be professionally installed with either a vented tap or the included kit, which contains a pressure reducing valve (PRV), pressure-limiting valve (PLV), shutoff valve, stainless steel connectors and a drain clamp.

PLUMBING CONNECTIONS: Both the inlet and outlet are recessed 1/4" stainless steel pipes. Quick connect stainless steel fittings are included in the above mentioned installation kit.

ELECTRICAL: Certificate number 202240. 220-240v 50hz single phase. Full load current is 0.8 amps. A 1.5-metre power cord is supplied.

COOLING PERFORMANCE:

8 litres per hour at 8-10°C

Cooling Speed: From 27°C to 8°C in 20 minutes

Draw Off Capacity: 8 cups (150ml) below 10°C

SHIPPING WEIGHTS & DIMENSIONS

AL-IC8	WEIGHT	WIDTH	DEPTH	HEIGHT
NET	12.5kg	21cm	41cm	27cm
PACKED	14kg	23cm	46cm	30cm

WARRANTY

The Aqua L'eau AL-IC8 undersink chiller is covered by a 3-year comprehensive warranty (copy available on request). The warranty provides comprehensive parts and labour coverage for the period of 3 years from the date of original sale.



FAUCET OPTIONS

